

6MBI35S-140

IGBT Modules

IGBT MODULE (S series) 1400V / 35A 6 in one-package

■ Features

- Compact Package
- P.C.Board Mount Module
- Low $V_{CE(sat)}$

■ Applications

- Inverter for Motor drive
- AC and DC Servo drive amplifier
- Uninterruptible power supply
- Industrial machines, such as Welding machines

■ Maximum ratings and characteristics

● Absolute maximum ratings (at $T_c=25^{\circ}\text{C}$ unless otherwise specified)

Item			Symbol	Rating	Unit
Collector-Emitter voltage			V _{CES}	1400	V
Gate-Emitter voltage			V _{GES}	±20	V
Collector current	Continuous	T _J =25°C	I _c	50	A
		T _J =75°C		35	
	1ms	T _J =25°C	I _c pulse	100	A
		T _J =75°C		70	
			-I _c	35	A
	1ms		-I _c pulse	70	A
Max. power dissipation (1 device)			P _c	240	W
Operating temperature			T _J	+150	°C
Storage temperature			T _{stg}	-40 to +125	°C
Isolation voltage *1			V _{is}	AC 2500 (1min.)	V
Screw torque			Mounting *2	3.5	N·m

*1: All terminals should be connected together when isolation test will be done.

*2: Recommendable value : 2.5 to 3.5 N·m (M5)

● Electrical characteristics (at $T_j=25^{\circ}\text{C}$ unless otherwise specified)

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	I_{CES}	—	—	1.0	$V_{GE}=0\text{V}$, $V_{CE}=1400\text{V}$	mA
Gate-Emitter leakage current	I_{GES}	—	—	0.2	$V_{CE}=0\text{V}$, $V_{GE}=\pm 20\text{V}$	μA
Gate-Emitter threshold voltage	$V_{GE(th)}$	5.5	7.2	8.5	$V_{CE}=20\text{V}$, $I_c=35\text{mA}$	V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	—	2.4	2.75	$T_j=25^{\circ}\text{C}$, $V_{GE}=15\text{V}$, $I_c=35\text{A}$	V
		—	3.0	—	$T_j=125^{\circ}\text{C}$	
Input capacitance	C_{ies}	—	4200	—	$V_{GE}=0\text{V}$	pF
Output capacitance	C_{oes}	—	875	—	$V_{CE}=10\text{V}$	
Reverse transfer capacitance	C_{res}	—	770	—	$f=1\text{MHz}$	
Turn-on time	t_{on}	—	0.35	1.2	$V_{CC}=800\text{V}$	μs
	t_r	—	0.25	0.6	$I_c=35\text{A}$	
	$t_{r(i)}$	—	0.1	—	$V_{GE}=\pm 15\text{V}$	
Turn-off time	t_{off}	—	0.45	1.0	$R_G=33\Omega$	
	t_f	—	0.08	0.3		
Diode forward on voltage	V_F	—	2.6	3.4	$T_j=25^{\circ}\text{C}$, $I_F=35\text{A}$, $V_{GE}=0\text{V}$	V
		—	2.2	—	$T_j=125^{\circ}\text{C}$	
Reverse recovery time	t_{rr}	—	—	0.35	$I_F=35\text{A}$	μs


● Thermal resistance characteristics

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	$R_{th(j-c)}$	—	—	0.52	IGBT	$^{\circ}\text{C/W}$
	$R_{th(j-c)}$	—	—	0.90	FWD	$^{\circ}\text{C/W}$
	$R_{th(c-f)*2}$	—	0.05	—	the base to cooling fin	$^{\circ}\text{C/W}$







*2 : This is the value which is defined mounting on the additional cooling fin with thermal compound












■ Equivalent Circuit Schematic



Characteristics







■ Outline Drawings, mm

mass : 180g

