

Thyristor Module

$$V_{RRM} = 2 \times 1600 \text{ V}$$


$$I_{TAV} = 27 \text{ A}$$

$$V_T = 1.27 \text{ V}$$

Phase leg


Part number

MCC26-16io8B



Backside: isolated

 E72873



Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability
- Direct Copper Bonded Al₂O₃-ceramic

Applications:

- Line rectifying 50/60 Hz
- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control

Package: TO-240AA

- Isolation Voltage: 4800 V~
- Industry standard outline
- RoHS compliant
- Soldering pins for PCB mounting
- Base plate: DCB ceramic
- Reduced weight
- Advanced power cycling


Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.



Thyristor				Ratings			
Symbol	Definition	Conditions		min.	typ.	max.	Unit
$V_{RSM/DSM}$	max. non-repetitive reverse/forward blocking voltage	$T_{VJ} = 25^{\circ}\text{C}$				1700	V
$V_{RRM/DRM}$	max. repetitive reverse/forward blocking voltage	$T_{VJ} = 25^{\circ}\text{C}$				1600	V
$I_{R/D}$	reverse current, drain current	$V_{R/D} = 1600\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$			100	μA
		$V_{R/D} = 1600\text{ V}$	$T_{VJ} = 125^{\circ}\text{C}$			3	mA
V_T	forward voltage drop	$I_T = 40\text{ A}$	$T_{VJ} = 25^{\circ}\text{C}$			1.27	V
		$I_T = 80\text{ A}$				1.64	V
		$I_T = 40\text{ A}$	$T_{VJ} = 125^{\circ}\text{C}$			1.27	V
		$I_T = 80\text{ A}$				1.65	V
I_{TAV}	average forward current	$T_C = 85^{\circ}\text{C}$	$T_{VJ} = 125^{\circ}\text{C}$			27	A
$I_{T(RMS)}$	RMS forward current	180° sine				42	A
V_{T0}	threshold voltage	} for power loss calculation only	$T_{VJ} = 125^{\circ}\text{C}$			0.85	V
r_T	slope resistance					11	m Ω
R_{thJC}	thermal resistance junction to case					0.88	K/W
R_{thCH}	thermal resistance case to heatsink				0.2		K/W
P_{tot}	total power dissipation		$T_C = 25^{\circ}\text{C}$			115	W
I_{TSM}	max. forward surge current	$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 45^{\circ}\text{C}$			520	A
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			560	A
		$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 125^{\circ}\text{C}$			440	A
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			475	A
I^2t	value for fusing	$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 45^{\circ}\text{C}$			1.35	kA ² s
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			1.31	kA ² s
		$t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$	$T_{VJ} = 125^{\circ}\text{C}$			970	A ² s
		$t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$	$V_R = 0\text{ V}$			940	A ² s
C_J	junction capacitance	$V_R = 400\text{ V}$ $f = 1\text{ MHz}$	$T_{VJ} = 25^{\circ}\text{C}$		22		pF
P_{GM}	max. gate power dissipation	$t_p = 30\text{ }\mu\text{s}$	$T_C = 125^{\circ}\text{C}$			10	W
		$t_p = 300\text{ }\mu\text{s}$				5	W
P_{GAV}	average gate power dissipation					0.5	W
$(di/dt)_{cr}$	critical rate of rise of current	$T_{VJ} = 125^{\circ}\text{C}; f = 50\text{ Hz}$ repetitive, $I_T = 45\text{ A}$				150	A/ μs
		$t_p = 200\text{ }\mu\text{s}; di_G/dt = 0.45\text{ A}/\mu\text{s};$ $I_G = 0.45\text{ A}; V = \frac{2}{3} V_{DRM}$ non-repet., $I_T = 27\text{ A}$				500	A/ μs
$(dv/dt)_{cr}$	critical rate of rise of voltage	$V = \frac{2}{3} V_{DRM}$	$T_{VJ} = 125^{\circ}\text{C}$			1000	V/ μs
		$R_{GK} = \infty$; method 1 (linear voltage rise)					
V_{GT}	gate trigger voltage	$V_D = 6\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$			1.5	V
			$T_{VJ} = -40^{\circ}\text{C}$			1.6	V
I_{GT}	gate trigger current	$V_D = 6\text{ V}$	$T_{VJ} = 25^{\circ}\text{C}$			100	mA
			$T_{VJ} = -40^{\circ}\text{C}$			200	mA
V_{GD}	gate non-trigger voltage	$V_D = \frac{2}{3} V_{DRM}$	$T_{VJ} = 125^{\circ}\text{C}$			0.2	V
I_{GD}	gate non-trigger current					10	mA
I_L	latching current	$t_p = 10\text{ }\mu\text{s}$	$T_{VJ} = 25^{\circ}\text{C}$			450	mA
		$I_G = 0.45\text{ A}; di_G/dt = 0.45\text{ A}/\mu\text{s}$					
I_H	holding current	$V_D = 6\text{ V}$ $R_{GK} = \infty$	$T_{VJ} = 25^{\circ}\text{C}$			200	mA
t_{gd}	gate controlled delay time	$V_D = \frac{1}{2} V_{DRM}$	$T_{VJ} = 25^{\circ}\text{C}$			2	μs
		$I_G = 0.45\text{ A}; di_G/dt = 0.45\text{ A}/\mu\text{s}$					
t_q	turn-off time	$V_R = 100\text{ V}; I_T = 20\text{ A}; V = \frac{2}{3} V_{DRM}$ $T_{VJ} = 100^{\circ}\text{C}$ $di/dt = 10\text{ A}/\mu\text{s}$ $dv/dt = 20\text{ V}/\mu\text{s}$ $t_p = 200\text{ }\mu\text{s}$			150		μs

Package TO-240AA				Ratings			
Symbol	Definition	Conditions		min.	typ.	max.	Unit
I_{RMS}	RMS current	per terminal				200	A
T_{VJ}	virtual junction temperature			-40		125	°C
T_{op}	operation temperature			-40		100	°C
T_{stg}	storage temperature			-40		125	°C
Weight					81		g
M_D	mounting torque			2.5		4	Nm
M_T	terminal torque			2.5		4	Nm
$d_{Spp/App}$	creepage distance on surface striking distance through air	terminal to terminal	13.0	9.7			mm
$d_{Spb/Apb}$		terminal to backside	16.0	16.0			mm
V_{ISOL}	isolation voltage	t = 1 second	50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA	4800			V
		t = 1 minute		4000			V




Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	MCC26-16io8B	MCC26-16io8B	Box	36	457825

Similar Part	Package	Voltage class
MCMA35P1600TA	TO-240AA-1B	1600
MCMA50P1600TA	TO-240AA-1B	1600

Equivalent Circuits for Simulation

* on die level


$T_{VJ} = 125^{\circ}\text{C}$

		Thyristor	
$V_{0\max}$	threshold voltage	0.85	V
$R_{0\max}$	slope resistance *	9.8	mΩ

Technical drawing of a 5-pin DIN connector. The drawing shows the front and side views with the following dimensions and labels:

- Overall width: 92 ± 0.5
- Distance from left edge to center of pin 1: 80 ± 0.3
- Pin 1 thread: M5
- Pin 1 diameter: 10 ± 0.1
- Pin 1 height: 14.8
- Pin 1 to pin 2 distance: 5.5 ± 0.1
- Pin 2 diameter: 10 ± 0.1
- Pin 2 height: 14.8
- Pin 3 diameter: 10 ± 0.1
- Pin 3 height: 14.8
- Pin 4 diameter: 10 ± 0.1
- Pin 4 height: 14.8
- Pin 5 diameter: 10 ± 0.1
- Pin 5 height: 14.8
- Pin 6 diameter: 10 ± 0.1
- Pin 6 height: 14.8
- Pin 7 diameter: 10 ± 0.1
- Pin 7 height: 14.8
- Pin 8 diameter: 10 ± 0.1
- Pin 8 height: 14.8
- Pin 9 diameter: 10 ± 0.1
- Pin 9 height: 14.8
- Pin 10 diameter: 10 ± 0.1
- Pin 10 height: 14.8
- Pin 11 diameter: 10 ± 0.1
- Pin 11 height: 14.8
- Pin 12 diameter: 10 ± 0.1
- Pin 12 height: 14.8
- Pin 13 diameter: 10 ± 0.1
- Pin 13 height: 14.8
- Pin 14 diameter: 10 ± 0.1
- Pin 14 height: 14.8
- Pin 15 diameter: 10 ± 0.1
- Pin 15 height: 14.8
- Pin 16 diameter: 10 ± 0.1
- Pin 16 height: 14.8
- Pin 17 diameter: 10 ± 0.1
- Pin 17 height: 14.8
- Pin 18 diameter: 10 ± 0.1
- Pin 18 height: 14.8
- Pin 19 diameter: 10 ± 0.1
- Pin 19 height: 14.8
- Pin 20 diameter: 10 ± 0.1
- Pin 20 height: 14.8
- Pin 21 diameter: 10 ± 0.1
- Pin 21 height: 14.8
- Pin 22 diameter: 10 ± 0.1
- Pin 22 height: 14.8
- Pin 23 diameter: 10 ± 0.1
- Pin 23 height: 14.8
- Pin 24 diameter: 10 ± 0.1
- Pin 24 height: 14.8
- Pin 25 diameter: 10 ± 0.1
- Pin 25 height: 14.8
- Pin 26 diameter: 10 ± 0.1
- Pin 26 height: 14.8
- Pin 27 diameter: 10 ± 0.1
- Pin 27 height: 14.8
- Pin 28 diameter: 10 ± 0.1
- Pin 28 height: 14.8
- Pin 29 diameter: 10 ± 0.1
- Pin 29 height: 14.8
- Pin 30 diameter: 10 ± 0.1
- Pin 30 height: 14.8
- Pin 31 diameter: 10 ± 0.1
- Pin 31 height: 14.8
- Pin 32 diameter: 10 ± 0.1
- Pin 32 height: 14.8
- Pin 33 diameter: 10 ± 0.1
- Pin 33 height: 14.8
- Pin 34 diameter: 10 ± 0.1
- Pin 34 height: 14.8
- Pin 35 diameter: 10 ± 0.1
- Pin 35 height: 14.8
- Pin 36 diameter: 10 ± 0.1
- Pin 36 height: 14.8
- Pin 37 diameter: 10 ± 0.1
- Pin 37 height: 14.8
- Pin 38 diameter: 10 ± 0.1
- Pin 38 height: 14.8
- Pin 39 diameter: 10 ± 0.1
- Pin 39 height: 14.8
- Pin 40 diameter: 10 ± 0.1
- Pin 40 height: 14.8
- Pin 41 diameter: 10 ± 0.1
- Pin 41 height: 14.8
- Pin 42 diameter: 10 ± 0.1
- Pin 42 height: 14.8
- Pin 43 diameter: 10 ± 0.1
- Pin 43 height: 14.8
- Pin 44 diameter: 10 ± 0.1
- Pin 44 height: 14.8
- Pin 45 diameter: 10 ± 0.1
- Pin 45 height: 14.8
- Pin 46 diameter: 10 ± 0.1
- Pin 46 height: 14.8
- Pin 47 diameter: 10 ± 0.1
- Pin 47 height: 14.8
- Pin 48 diameter: 10 ± 0.1
- Pin 48 height: 14.8
- Pin 49 diameter: 10 ± 0.1
- Pin 49 height: 14.8
- Pin 50 diameter: 10 ± 0.1
- Pin 50 height: 14.8
- Pin 51 diameter: 10 ± 0.1
- Pin 51 height: 14.8
- Pin 52 diameter: 10 ± 0.1
- Pin 52 height: 14.8
- Pin 53 diameter: 10 ± 0.1
- Pin 53 height: 14.8
- Pin 54 diameter: 10 ± 0.1
- Pin 54 height: 14.8
- Pin 55 diameter: 10 ± 0.1
- Pin 55 height: 14.8
- Pin 56 diameter: 10 ± 0.1
- Pin 56 height: 14.8
- Pin 57 diameter: 10 ± 0.1
- Pin 57 height: 14.8
- Pin 58 diameter: 10 ± 0.1
- Pin 58 height: 14.8
- Pin 59 diameter: 10 ± 0.1
- Pin 59 height: 14.8
- Pin 60 diameter: 10 ± 0.1
- Pin 60 height: 14.8
- Pin 61 diameter: 10 ± 0.1
- Pin 61 height: 14.8
- Pin 62 diameter: 10 ± 0.1
- Pin 62 height: 14.8
- Pin 63 diameter: 10 ± 0.1
- Pin 63 height: 14.8
- Pin 64 diameter: 10 ± 0.1
- Pin 64 height: 14.8
- Pin 65 diameter: 10 ± 0.1
- Pin 65 height: 14.8
- Pin 66 diameter: 10 ± 0.1
- Pin 66 height: 14.8
- Pin 67 diameter: 10 ± 0.1
- Pin 67 height: 14.8
- Pin 68 diameter: 10 ± 0.1
- Pin 68 height: 14.8
- Pin 69 diameter: 10 ± 0.1
- Pin 69 height: 14.8
- Pin 70 diameter: 10 ± 0.1
- Pin 70 height: 14.8
- Pin 71 diameter: 10 ± 0.1
- Pin 71 height: 14.8
- Pin 72 diameter: 10 ± 0.1
- Pin 72 height: 14.8
- Pin 73 diameter: 10 ± 0.1
- Pin 73 height: 14.8
- Pin 74 diameter: 10 ± 0.1
- Pin 74 height: 14.8
- Pin 75 diameter: 10 ± 0.1
- Pin 75 height: 14.8
- Pin 76 diameter: 10 ± 0.1
- Pin 76 height: 14.8
- Pin 77 diameter: 10 ± 0.1
- Pin 77 height: 14.8
- Pin 78 diameter: 10 ± 0.1
- Pin 78 height: 14.8
- Pin 79 diameter: 10 ± 0.1
- Pin 79 height: 14.8
- Pin 80 diameter: 10 ± 0.1
- Pin 80 height: 14.8
- Pin 81 diameter: 10 ± 0.1
- Pin 81 height: 14.8
- Pin 82 diameter: 10 ± 0.1
- Pin 82 height: 14.8
- Pin 83 diameter: 10 ± 0.1
- Pin 83 height: 14.8
- Pin 84 diameter: 10 ± 0.1
- Pin 84 height: 14.8
- Pin 85 diameter: 10 ± 0.1
- Pin 85 height: 14.8
- Pin 86 diameter: 10 ± 0.1
- Pin 86 height: 14.8
- Pin 87 diameter: 1

Type ZY 200R (R = Right for pin pair 6/7) } UL 758, style 3751



Thyristor




Fig. 1 Surge overload current I_{TSM} ,
 I_{FSM} : Crest value, t : duration




Fig. 2 I^2t versus time (1-10 ms)




Fig. 3 Max. forward current
 at case temperature




Fig. 4 Power dissipation vs. on-state current & ambient temperature
 (per thyristor or diode)




Fig. 5 Gate trigger characteristics




Fig. 6 Three phase rectifier bridge: Power dissipation versus direct
 output current and ambient temperature




Fig. 7 Gate trigger delay time

Thyristor




Fig. 8 Three phase AC-controller: Power dissipation versus RMS output current and ambient temperature




Fig. 9 Transient thermal impedance junction to case (per thyristor/diode)

R_{thJC} for various conduction angles d:

d	R_{thJC} [K/W]
DC	0.88
180°	0.92
120°	0.95
60°	0.98
30°	1.01

Constants for Z_{thJC} calculation:

i	R_{thi} [K/W]	t_i [s]
1	0.019	0.0031
2	0.029	0.0216
3	0.832	0.1910




Fig. 10 Transient thermal impedance junction to heatsink (per thyristor/diode)

R_{thJK} for various conduction angles d:

d	R_{thJK} [K/W]
DC	1.08
180°	1.12
120°	1.15
60°	1.18
30°	1.21

Constants for Z_{thJK} calculation:

i	R_{thi} [K/W]	t_i [s]
1	0.019	0.0031
2	0.029	0.0216
3	0.832	0.1910
4	0.200	0.4500