


MG300Q2YS60A(1200V/300A 2in1)

High Power Switching Applications

Motor Control Applications

- Integrates a complete half bridge power circuit and fault-signal output circuit in one package.
(short circuit and over temperature)
- The electrodes are isolated from case.
- Low thermal resistance
- $V_{CE(sat)} = 2.4 \text{ V (typ.)}$


Equivalent Circuit



Signal terminal

1.	G (L)	2.	F _O (L)	3.	E (L)	4.	V _D
5.	G (H)	6.	F _O (H)	7.	E (H)	8.	Open

Unit: mm



Technical drawing of a 16-pin connector. The drawing shows a rectangular component with two circular end views. The top view is divided into two sections, each containing four pins. The pins are numbered 1 through 8. The dimensions are given as 25.4 ± 0.6 mm for the overall height and 2.54 mm for the pin pitch and width.

- | | | | | | | | |
|----|-------|----|--------------------|----|-------|----|----------------|
| 1. | G (L) | 2. | F _O (L) | 3. | E (L) | 4. | V _D |
| 5. | G (H) | 6. | F _O (H) | 7. | E (H) | 8. | Open |

Weight: 375 g

Maximum Ratings (Ta = 25°C)

Stage	Characteristics		Symbol	Rating	Unit
Inverter	Collector-emitter voltage		V_{CES}	1200	V
	Gate-emitter voltage		V_{GES}	±20	V
	Collector current	DC	I_C	300	A
		1 ms	I_{CP}	600	
	Forward current	DC	I_F	300	A
		1 ms	I_{FM}	600	
	Collector power dissipation (Tc = 25°C)		P_C	2800	W
Control	Control voltage (OT)		V_D	20	V
	Fault input voltage		V_{FO}	20	V
	Fault input current		I_{FO}	20	mA
Module	Junction temperature		T_j	150	°C
	Storage temperature range		T_{stg}	−40~125	°C
	Operation temperature range		T_{ope}	−20~100	°C
	Isolation voltage		V_{isol}	2500 (AC 1 min)	V
	Screw torque		—	3 (M5)	N·m

Electrical Characteristics (Tj = 25°C)

1. Inverter Stage

Characteristics		Symbol	Test Condition		Min	Typ.	Max	Unit
Gate leakage current		I _{GES}	V _{GE} = ±20 V, V _{CE} = 0		—	—	+3/−4	mA
			V _{GE} = +10 V, V _{CE} = 0		—	—	100	nA
Collector cut-off current		I _{CES}	V _{CE} = 1200 V, V _{GE} = 0		—	—	1.0	mA
Gate-emitter cut-off voltage		V _{GE (off)}	V _{CE} = 5 V, I _C = 300 mA		6.0	7.0	8.0	V
Collector-emitter saturation voltage		V _{CE (sat)}	V _{GE} = 15 V, I _C = 300 A	T _J = 25°C	—	2.4	2.8	V
				T _J = 125°C	—	—	3.2	
Input capacitance		C _{ies}	V _{CE} = 10 V, V _{GE} = 0, f = 1 MHz		—	21000	—	pF
Switching time	Turn-on delay time	t _{d (on)}	V _{CC} = 600 V, I _C = 300 A V _{GE} = ±15 V, R _G = 6.8 Ω (Note 1)		0.10	—	1.00	μs
	Turn-off time	t _{off}			—	—	2.00	
	Fall time	t _f			—	—	0.50	
Reverse recovery time		t _{rr}			—	—	0.50	
Forward voltage		V _F	I _F = 300 A		—	2.1	2.6	V

Note 1: Switching time test circuit & timing chart


2. Control (Tc = 25°C)

Characteristics	Symbol	Test Condition	Min	Typ.	Max	Unit
Fault output current	OC	$V_{GE} = 15 \text{ V}$	360	—	—	A
Over temperature	OT	—	100	—	125	°C
Fault output delay time	$t_d \text{ (Fo)}$	$V_{CC} = 600 \text{ V}, V_{GE} = \pm 15 \text{ V}$	—	—	8	μs


3. Module (Tc = 25°C)

Characteristics	Symbol	Test Condition	Min	Typ.	Max	Unit
Junction to case thermal resistance	$R_{th(j-c)}$	Inverter IGBT stage	—	—	0.044	°C/W
		Inverter FRD stage	—	—	0.068	
Case to fin thermal resistance	$R_{th(c-f)}$	With silicon compound	—	0.013	—	°C/W

Switching Time Test Circuit



Timing Chart















Remark**<Short circuit capability condition>**







- Short circuit capability is 6 μ s after fault output signal.
Please keep following condition to use fault output signal.
 - $V_{CC} \leq 750 \text{ V}$
 - $14.8 \text{ V} \leq V_{GE} \leq 17.0 \text{ V}$
 - $R_G \geq 6.8 \text{ } \Omega$
 - $T_j \leq 125^\circ\text{C}$

<Gate voltage>

- To use this product, V_{GE} must be provided higher than 14.8 V.
In case V_{GE} is less than 14.8 V, fault signal FO may not be output even under error conditions.







RESTRICTIONS ON PRODUCT USE

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.